



PRODUCT	SIZES (MM)						WEIGHT (KG)	MAXIMUM LOAD (KG)
	A	B	C	D	E	F		
JOLLY 200R2-50 Fixed base and belt attachment	520	610	1080	565	215	2050	23	300
JOLLY 200R2-50 Removable base	520	610	1080	725	110	2050	23	300
JOLLY 200R2-50 Fixed base	520	610	1080	553	110	2050	23	300
JOLLY 200R2-64 Removable base	640	730	1080	845	110	2050	25	300

- A Useful width of the passage
- B Maximum overall dimensions
- C Closed ramp height
- D Maximum base width
- E Thickness
- F Length
- R Number of stages



MOVIA JOLLY RAMP

The choice to build this article arises from the strong demand in market (until now dominated by artisan products) of a solid, industrialized, high quality and competitively priced product, for the transport of people on dialysis.

This **RAMP**, made with the highest quality materials and powder coated, is 200 cm long and has a walking surface completely in aluminum of 52cm or 64cm. The outer lanes are smooth to allow the wheels to slide smoothly, while the central part is equipped with special punching to ensure optimal grip for the operator.

The capacity is 300 kg, the height encumbrance of the ramp is only 108 cm.

SUPER LIGHT
Only 23 kg Like all our ramps, it is **REMOVABLE** simply by unscrewing the appropriate knobs, thus guaranteeing enormous versatility to the vehicle in which it is installed, so it can also be used for other types of services.